



SPEEDY WASH 626, una macchina completamente autonoma, alimentata da batterie da 24V CC, senza cavi di collegamento.

Due velocità di trazione, flessibile nelle manovre, rispettosa dell'ambiente (zero emissioni) e silenziosa. Può lavorare sia all'esterno che all'interno del garage.

In pochi minuti può far splendere il vostro veicolo senza fatica, in economia e sicurezza.

The 24V battery drive 626 LX is ideal for washing up to 40 buses or trailers on one charge, quietly and emission-free, indoors or outdoors.

This amazing, first ever battery operated totally self contained washing machine provides an autonomous two-speed power-brush which can be operated with minimal effort, in two directions. With the 626 LX, your vehicles will regain their shine effortlessly and economically. Options such as the closed-pore-foam 'Brill' brush and the detergent application system (also available on other models) have made the 626 LX a best seller on 5 continents.

SCHEMA TECNICA: SPEEDY WASH 626 LX			
		u.m.	
CARATTERISTICHE	Alimentazione	-	Batteria 24V
	Sistema di guida	-	Ruota centrale motorizzata e doppia maniglia di comando
	Inclinazione spazzola	gradi	10°
	Alimentazione inclinazione spazzola	-	Elettrica 24V
	Alimentazione rotazione spazzola	-	Elettrica 24V
	Alimentazione trazione	-	Elettrica 24V
	Peso a pieno carico	Kg	960
	Peso a vuoto	Kg	540
	DIMENSIONI	Altezza totale con spazzola standard	cm
Altezza effettiva di lavaggio		cm	410
Dimensioni base		cm	105x120
Diametro spazzola		cm	103
PRESTAZIONI	Capacità serbatoio acqua	L	420
	Giri spazzola	RPM	100
	Potenza motore spazzola	KW	1
	Velocità lavaggio	m/min	20
	Velocità spostamento	m/min	40

SPECIFICATIONS: SPEEDY WASH 626 LX			
		u.m.	
FEATURES	Power supply	-	Battery 24V
	Traction and steering	-	Central motorized wheel and dual handle controls
	Brush inclination	Degrees	0°- 10°
	Inclination system power supply	-	Electric 24V
	Brush rotation power supply	-	Electric 24V
	Traction system	-	Electric 24V
	Weight loaded	Lbs	2112
	Weight empty	Lbs	1188
DIMENSIONS	Overall height with standard brush	ft.	13'10"
	Effective wash height	ft.	13'6"
	Base size	ft.	3'6" x 4'
	Brush diameter	ft.	3'5"
PERFORMANCE	Water tank capacity	Gal.	112
	Brush revolutions per minute	RPM	100
	Output of brush engine	KW	1
	Washing speed	Ft/m.	66'
	Travel speed	Ft/m.	112'